EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L2	1798	status with statement	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:46
L3	963	status near5 statement	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:46
L4	4	status near5 statement with source adj code	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:46
L5	146	(status with statement).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:48
L6	18	5 and source adj code	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:48
L7	689	717/110-113.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:50
L8	4	2 and 7	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:50
L9	0	"717"".""140".ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:52

L10	811	717/140.ccls.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:52
L11	9	2 and 10	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	AND	ON	2008/02/01 20:52

Google Scholar BETA

source code statement AND copy | merge | pa   - 2003   Search | Ad Sc Sc

The **"AND"** operator is unnecessary -- we include all search terms by default. [details]

Scholar   All articles - Recent articles Results **1 - 10** of about **40,800** for source code statement ANI

All Results

J Corbett

M Fowler

M Hatcliff

J Laubach

S Pasareanu

Bandera: extracting finite-state models from Java source code - all 17 versions »
JC Corbett, MB Hatcliff, J Laubach, S Pasareanu, ... - Software Engineering, 2000. Proceedings of the 2000 ..., 2000 - ieeexplore.ieee.org
... checker counter-example traces back to source code traces ... Thus, after specialization, a single Java source node may ... a program P and some statements of interest ...
Cited by 721 - Related Articles - Web Search

CCFinder: a multilinguistic token-based code clone detection system for large scale source code - all 10 versions »
T Kamiya, S Kusumoto, K Inoue - Software Engineering, IEEE Transactions on, 2002 - ieeexplore.ieee.org
... or so) and that the length of this caller statement is USELEN ... In this case, vix□g□ Â □y□□g□ code portions are occupied in the original source files. ...
Cited by 231 - Related Articles - Web Search

Using Slicing to Identify Duplication in Source Code - all 11 versions »
R Komondoor, S Horwitz - Static Analysis: 8th International Symposium, SAS 2001, ..., 2001 - books.google.com
... Using Slicing to Identify Duplication in Source Code 55 our ... clones that involve variable renaming and statement reordering ... is a good one; real code does include ...
Cited by 102 - Related Articles - Web Search

DOC: a practical approach to source-level debugging of globally optimized code
DS Coutant, S Meloy, M Ruscetta - Proceedings of the ACM SIGPLAN 1988 conference on ..., 1988 - portal.acm.org
... The first instruction generated for a source statement will be referred to as a senhy (statement entry). ... by a flag which is set by the code generator when ...
Cited by 60 - Related Articles - Web Search

The program dependence graph in a software development environment
KJ Ottenstein, LM Ottenstein - ACM SIGSOFT Software Engineering Notes, 1984 - portal.acm.org
... fact sufficient for many optimization and code generation algorithms ... selects a variable, expression or statement in a ... The augmented source file points to the ...
Cited by 399 - Related Articles - Web Search

[RTF] Zstep 95: A reversible, animated source code stepper - all 2 versions »
H Lieberman, C Fry - Software Visualization: Programming as a Multimedia ..., 1997 - media.mit.edu
... Rather than inserting breakpoints or print statements into the actual code ... The top window contained an unmodified copy of the source code, annotated just by ...
Cited by 48 - Related Articles - View as HTML - Web Search

[BOOK] GENOA: a customizable language-and front-end independent **code** analyzer - all 6 versions »
PT Devanbu - 1992 - ACM Press New York, NY, USA
... To **copy** otherwise, or to republish, requires a fee and/or specific permission. ... current node). For each assignment **statement** node, we ... from C **source code**. ...
Cited by 115 - Related Articles - Web Search

Method and apparatus for translating **source code** from one high-level computer language to another - all 7 versions »
KA Andrews, P Del Vigna, ME Molloy - US Patent 5,768,564, 1998 - Google Patents
... illustration, **show** preferred embodiments of the present ... various architecture-specific and **source** syntax tree ... such as assembly language **code statements** and ...
Cited by 40 - Related Articles - Web Search

Source transformation in software engineering using the TXL transformation system - all 10 versions »
JR Cordy, TR Dean, AJ Malton, KA Schneider - Information and Software Technology, 2002 - Elsevier
... For larger SELECT **statements**, the difference is even more ... Design recovery from **source**. ...
between design documents and actual implementation **code** throughout the ...
Cited by 99 - Related Articles - Web Search

The case for high-level parallel programming in ZPL - all 4 versions »
BL Chamberlain, SE Choi, EC Lewis, L Snyder, WD ... - Computational Science and Engineering, IEEE [see also ..., 1998 - ieeexplore.ieee.org
... is given a default value—in the **source code**—that the ... elsewhere.)4 Second, regions can specify a **statement**'s domain ... of size 2. Lines 16—20 **show** the **code** ...
Cited by 42 - Related Articles - Web Search

Goooooooooogle ▶

Result Page: **1** 2 3 4 5 6 7 8 9 10   **Next**

| source code statement AND copy | r | Search |

Google Home - About Google - About Google Scholar

Google

| text editor update OR set source code stateme | Search | Advanced Search Preferences |

Web Results **1 - 10** of about **160,000** for <u>text</u> <u>editor</u> <u>update</u> OR <u>set</u> <u>source code</u> <u>statement</u> <u>status</u> . (0.22 seco

Tip: Save time by hitting the return key instead of clicking on "search"

Xcode User Guide: **Text Editor**
Regardless of your choice, Xcode uses a common **text editor** view. .... appear in the
Function menu, use the #pragma mark **statement** in your **source code**. ...
developer.apple.com/.../Contents/R**e**sources/
en.lproj/03_03_editing_**editor**_window/chapter_22_section_2.html - 27k -
<u>Cached</u> - <u>Similar pages</u>

[Chapter 23] 23.6 Using SQL to Examine Stored Objects
You can view the **source code** of a stored object with the SQL **statement** shown below. ...
IF obj_cur%FOUND THEN **UPDATE SOURCE$ SET source** = REPLACE (**source,** ...
www.unix.org.ua/orelly/oracle/prog2/ch23_06.htm - 27k - <u>Cached</u> - <u>Similar pages</u>

Web Wiz Rich **Text Editor** - Features
The resulting **source code** is then submitted like any other textarea. Main Features. Web
Wiz Rich **Text Editor** is simple to setup but has the power to protect ...
www.webwizguide.com/webwizrich**texteditor**/features.asp - 32k - <u>Cached</u> - <u>Similar pages</u>

Data Structures in the Andrew **Text Editor**
In the right column are the **editor** working on this document and another **editor** where I am
checking **source code**. This article attempts to describe how the ...
www.cs.cmu.edu/~wjh/papers/byte.html - 28k - <u>Cached</u> - <u>Similar pages</u>

SourceForge.net: **SET's Editor, a friendly text editor**
Perl and a Java **source** file, and the MP3 menu. (Linux/Eterm SETEdit is a friendly **text
editor**. It is a **text** mode application with windows, buttons, ...
sourceforge.net/projects/setedit/ - 33k - <u>Cached</u> - <u>Similar pages</u>

mozilla.org **status update**
Akkana Peck has our **Editor update**::. We stabilized M5 and began working on our M6
features (see ... "This week Netscape released the **source code** to Rhino, ...
www.mozilla.org/**status**/1999-5-7.html - 23k - <u>Cached</u> - <u>Similar pages</u>

Java Tip 131: Make a **statement** with javac! - Java World
Next, write the **source code** to the file through a PrintWriter for convenience: ... We found
the meaning of each **status code** by decompiling javac , hence we ...
www.javaworld.com/javatips/jw-javatip131.html - 49k - <u>Cached</u> - <u>Similar pages</u>

RFC 76 (rfc76) - Connection by name: User oriented protocol
Example of User Dialogue Assume a user residing at CAC, whose site **code** is .... **Status
Statement <status statement> ::= STATUS <device class> | STATUS ...**
www.faqs.org/rfcs/rfc76.html - 28k - <u>Cached</u> - <u>Similar pages</u>

Manifest, GNU **Source Code** CD-ROM **set** #16
It works nicely with the Emacs **editor**, offers some nice features such as input ...... VRweb is
the only free VRML browser available in full **source code,** ...
www.gnu.org/order/**source**manifest.html - 77k - <u>Cached</u> - <u>Similar pages</u>

freshmeat.net: Project details for GTK2 Text Editor
GTK2 **Text Editor** is a simple Unicode **text editor** that supports many encodings. .... Sure, you can sell binary packages but you _must_ make the **source code ...**
freshmeat.net/projects/gtk2edit/ - 31k - Cached - Similar pages

1 2 3 4 5 6 7 8 9 10   **Next**

| text editor update OR set source coc | Search |

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve | Try Google Experimental

---

©2008 Google - Google Home - Advertising Programs - Business Solutions - About Google